

iQUBE2™

The ALL New Comprehensive Contamination Sorter

Highlights

- Best - in - Class for ALL Contaminants including Plastics
- Comprehensive Detection of various types of PP, including White and Transparent Strings
- Cutting Edge Technology based on Multi Spectrum Detection Analysis (MSDA)
- Direct connectivity with Final Beater of all Blow Room Lines with less space requirement
- Lowest Lint Loss



iQ
intelligent QUALITY

iQUBE2™

Technical Data *

Contaminations Detected

- All Plastics including Coloured / Transparent / White PolyPropylene Strings, Sheets, Films etc,
- Paper, Fabric, Feather, Jute bits etc,

Line Integration

- At end of the Blow Room Line, connected after beaters like Flexiclean, Supremoclean (LMW), Uniflex , A79R (Rieter), CVT or CLC (Trutzschler) and Fine Opener (Crosrol) or equivalent other makes
- Material Flow from Bottom to Top
- Input duct: 1100 x 80 mm

Key Technology

- Multi Spectrum Detection Analysis (MSDA) Technology
- Precise detection of All types of Contaminations using InfraRed, UV and UltraSonic Modules for effective detection of White PP

Power Supply

- Single Phase 1.5 kW Consumption (for machine electronics)
- Three Phase 0.75 kW Consumption (for evacuation motor)

Configuration

- Production rate up to 1500 kg/h
- Material velocity up to 20 m/sec
- Auto correction for tuft speed variations

Material Ejection

- Pneumatic ejection and Automatic removal of Ejected Material

Output Parameters

- Ejections : Shift wise and Mix wise
- Alarm for exceptions

Calibration

- Automatic and Manual Calibration

Ambient Conditions

- Relative humidity : 40 to 65%
- Temperature : 5° to 55°c

Compressed Air Requirement

- Approx 3 m³/hr at 6 Bar

* Subject to change without prior notice

premier evolvis pvt. ltd.

SF No. 79/6, Kulathur Road
Venkitapuram Post
Coimbatore - 641 062, India

Phone : +91 422 6611000

Fax : +91 422 6611005

E mail : sales@premier-1.com

www.premier-1.com



User Friendly Numerical and Graphical Reports

